

## **TREATMENT INSTRUCTIONS**

### **Diesel ENGINE Treatment**

**NOTE: Read through the entire instruction sheet before installing any Microlon Products.**

**To Install the Microlon Products-**

**1) Change your oil and oil filter. Change your fuel filter. Drain out an amount of oil equal to the amount of Compound 90 to be added to the crankcase.**

**2) Shake the Microlon containers for at least one minute.**

**3) Start the engine and bring it to operating temperature. Turn the engine off and add all of the Compound 90 to the crankcase. Add the Microlon Engine Treatment but do not exceed 20% of the total oil volume at any one time. It may be necessary to add the remaining product after the cleaners have done their job and left the engine.**

**4) Add the Microlon Fuel Treatment to a 1/2 tank of fuel.**

**5) Immediately operate the engine for at least one hour or 100 miles.**

**NOTE: Do not change your oil for at least 1,000 miles after treatment to make sure that you get the full benefits of a Microlon Engine Treatment.**

**NOTE: Microlon is compatible with all oils & fuels including synthetics.**

**Microlon, Inc 217 Trademark Dr. Buda, Texas 78610 USA**  
**Order Desk: (512) 295-9895 Toll Free Order Desk: (800) 962-4152**  
**Tech Support: (512) 247-8172 FAX: (512) 295-9896**