

TREATMENT INSTRUCTIONS

Marine ENGINE Treatment

NOTE: Read through the entire instruction sheet before installing any Microlon Products.

To Install the Microlon Products-

- 1) Change your oil and oil filter.**
- 2) Shake the Microlon containers for at least one minute.**
- 3) Start the engine and bring it to operating temperature. Turn the engine off and add the Engine Treatment to the crankcase, but do not exceed 20% of the total oil volume at any one time. It may be necessary to add the remaining product after the cleaners have done their job and left the engine.**
- 4) Change the fuel filter if possible. Add the Microlon Fuel Treatment to a 1/2 tank of fuel. The fuel treatment may be added later if needed.**
- 5) Immediately operate the engine for at least one hour or 100 miles. Driving is recommended, but idling is acceptable.**
- 6) Add the Compound 90. Drain out an amount of oil equal to the amount of Compound 90 to be added to the crankcase.**

NOTE: Do not change your oil for at least 1,000 miles after treatment to make sure that you get the full benefits of a Microlon Engine Treatment.

NOTE: Microlon is compatible with all oils & fuels including synthetics.

Microlon, Inc 217 Trademark Dr. Buda, Texas 78610 USA
Order Desk: (512) 295-9895 Toll Free Order Desk: (800) 962-4152
Tech Support: (512) 247-8172 FAX: (512) 295-9896